



FVO-400RC



FVNP-400RC

MODEL	FVO-400RC	FVNP-400RC
Heat Capacity	up to 390,000 btuh	up to 390,000 btuh
Fuel Tank Capacity/Run Time	42 US Gallons / 14 hrs	External
Heater Dimensions/Weight	70" x 29" x 54" / 450 lbs	70" x 29" x 54" / 365 lbs
Heater Exchanger	16 Gauge 304 Stainless Steel	16 Gauge 304 Stainless Steel
Air Circulation	4,000 CFM - Ductable up to 150ft	4,000 CFM - Ductable up to 150ft
Air Outlet/Inlet	Outlet - 2 x 12" Dia. or 1 x 16" Dia. Inlet - 1 x 16" Dia.	Outlet - 2 x 12" Dia. or 1 x 16" Dia. Inlet - 1 x 16" Dia.
Wheels	16" Dia. Flat Free Wheels	16" Dia. Flat Free Wheels
Power Requirements	115V / 15Amp (10.5 Amp Draw)	115V / 15Amp (10.5 Amp Draw)



FEATURES:

- Proven Riello burner technology including nozzle pre-heater for cold weather start up and upgraded low temperature fuel pump.
- Powerful backward incline blower provides ultra-quiet operation & low amperage, ductable up to 150FT.
- High density flat free wheels, smart power indicator control and volt meter.
- Optional: Tiger-loop fuel filter system that eliminates fuel system air locks & 118 US Gallon Fuel Tank.