



# HEPA-AIRE® NEGATIVE AIR MACHINES

## High CFM | Three Stages of Filtration | Easy Filter Removal

### H2KM & H2KMA

The H2KM & H2KMA negative air machines are the perfect units for contractors who want the very best in performance, reliability and quality.

#### FEATURES & BENEFITS

- One-horsepower, two speed motor delivers airflow of 2000 on High and 1300 on Low (CFM)
- At only 26 inches wide the H2KM and H2KMA fit easily through standard doorways
- Four heavy-duty, 4" casters (2 fixed and 2 locking swivels) provide mobility and maneuverability
- Standard filters include: 1 ea. polypad prefilter, 1 ea. pleated prefilter and 1 ea. 99.97% HEPA filter  
Optional 12" HEPA and high-capacity carbon filters are available
- H2KM is equipped with a visual "change filter" indicator lamp
- H2KMA is equipped with a differential pressure gauge and an audio "change filter" alarm
- The H2KM and H2KMA have been independently tested and certified in accordance with applicable UL and CSA safety requirements



H2KM

#### TECHNICAL SPECIFICATIONS

| DESCRIPTION                       | UNIT     | H2KM & H2KMA                                                                           |
|-----------------------------------|----------|----------------------------------------------------------------------------------------|
| Net Weight                        | lbs (kg) | 124 (56.25)                                                                            |
| Dimensions (L x W x H)            | in (cm)  | 35.75 x 26 x 30.25 (91 x 66 x 77)                                                      |
| Electrical Rating                 | V, Hz, A | 120 VAC, 60 Hz, 15 A                                                                   |
| Airflow,* Max.<br>w/Clean Filters | CFM      | 2000 High Speed, 1300 Low Speed                                                        |
| Normal Operating Amps             | A        | 10 or less                                                                             |
| Motor                             | -        | 1 HP, 2 speed motor with thermal overload protection, auto re-set, 60 Hz, single phase |
| Sound Level @ 5 Feet              | dBA      | 70 on high speed                                                                       |
| HEPA Filter Efficiency            | -        | 99.97% @ 0.3 microns                                                                   |
| Cabinet Material                  | -        | 20 gauge galvanized steel                                                              |
| Prefilter Access                  | -        | Swing out hinged door secured in place with cam latch                                  |
| First stage prefilter             | 1 ea     | H2001, polypad                                                                         |
| Second stage prefilter            | 1 ea     | H2002, 2" deep particulate pleat                                                       |
| Alternate Second Stage            | 1 ea     | VL2024, 2" deep high capacity carbon                                                   |
| HEPA Filter                       | 1 ea     | H242406-99, 6" deep 99.97% @ 0.3 microns                                               |
| Alternate HEPA Filter             | 1 ea     | H2010M, 12" deep 99.97% @ 0.3 microns                                                  |

Specifications and details are subject to change without prior notice.



H2KMA

\*Note: Airflow ratings estimates are based on factory and independent testing @ 120 VAC with an air straightener and a traverse of readings taken with a computing vane-anemometer. Actual results may vary for various reasons, including motor and blower and HEPA filter tolerances. Factors such as filter loading, reduced voltage to the motor, and inlet and outlet ducting will reduce airflow. Use these ratings as a general guideline only.

#### CONTACT US FOR MORE INFORMATION

**ABATEMENT**  
TECHNOLOGIES®  
LEADERS IN CLEAN AIR

USA  
1-800-634-9091  
ABATEMENT.COM  
IAQINFO@ABATEMENT.COM

CANADA  
1-800-827-6443  
ABATEMENT.CA  
IAQINFO@ABATEMENT.CA

#### THE H2KM & H2KMA ARE BEST SUITED FOR:



ABATEMENT & REMEDIATION



HEALTHCARE CONSTRUCTION